

# Supply range - Oil field tubes (OCTG)

Outside diameter		Wall thicknesses in mm / inch																	
mm	inch	5,2	5,6	6,3	7,1	8	8,8	10	11	12,7	13	13,8	14,3	15	16,1	17,5	20,6	22,2	25,4
		0,21	0,22	0,25	0,28	0,35	0,35	0,39	0,43	0,5	0,51	0,54	0,56	0,59	0,63	0,69	0,81	0,87	1
114,3	4 1/2	█	█																
139,7	5 1/2	█	█																
168,3	6 5/8	█	█	█	█	█	█	█											
177,8	7			█	█	█	█	█											
193,7	7 5/8			█	█	█	█	█	█										
219,1	8 5/8			█	█	█	█	█	█	█									
244,5	9 5/8			█	█	█	█	█	█	█									
273,0	10 3/4				█	█	█	█	█	█									
323,9	12 3/4				█	█	█	█	█	█	█								
339,7	13 3/8				█	█	█	█	█	█	█	█							
346,1	13 5/8				█	█	█	█	█	█	█	█	█						
355,6	14				█	█	█	█	█	█	█	█	█	█					
406,4	16				█	█	█	█	█	█	█	█	█	█	█				
473,1	18 5/8				█	█	█	█	█	█	█	█	█	█	█	█			
508,0	20				█	█	█	█	█	█	█	█	█	█	█	█	█		
530,0	21				█	█	█	█	█	█	█	█	█	█	█	█	█	█	
558,0	22				█	█	█	█	█	█	█	█	█	█	█	█	█	█	
610,0	24				█	█	█	█	█	█	█	█	█	█	█	█	█	█	

█ Grades H40, J55, J55 UPG, K55

█ Grades K55 FBN, N80Q, N80Q Weldable, L80, R95, P110 upon request

█ Grades H40, J55, J55 UPG, K55, K55 FBN, N80Q, N80Q Weldable, L80, R95, P110

max. 18.5 mm (0.728") for K55

Max. length:  
16 m (53ft) for P110, K55 FBN, L80, N80 Q, N80 Q Weldable, R95  
18 m (59ft) for H40, J55, J55 Weldable, J55 UPG, K55

High collapse resistance on request